

DEKUMA



DKM-RV300

## 应用范围/Applications

减震橡胶, 油封, O型圈, 制动皮碗, 皮膜, 门窗橡胶密封条接角  
Vibration absorption rubber, oil sealing, O-ring, braking rubber bowl, rubber mould, door and window sealing strip connecting, etc.



DEKUMA

## 机器参数/Machine Specifications

机型 Model	单位 Unit	DKM-RV200	DKM-RV300	DKM-RV400	DKM-RV500
注射压力 Injection Pressure	kg/cm <sup>2</sup>	1750	1750	1750	1660
注射容积 Injection Volume	CC	2000	3000	4000	5000
锁模力 Clamping Force	kN	2,000	3,000	4,000	5,000
开模行程 Mould Open Stroke	mm	480	570	600	760
热板间距 Distance between Heating Plates	mm	600	640	700	860
最少模厚 Min Mould Height	mm	120	70	100	100
热板尺寸 Heating Plate Dim.	mm	500X550	650X650	600X650	720X700
移模行程 Mould Slide Stroke	mm	600	650	650	800
系统压力 System Pressure	bar	225	200	210	220
机器重量 Machine Weight	ton	6.5	8.5	10	14.5
外形尺寸(长x宽x高) Machine Dimension (LxWxH)	m	3.7x2.2x3.7	3.9x2.4x4.1	3.7x2.45x4.9	3.9x3x5.16
油泵电机功率 Oil Pump Motor Power	kW	11	15	22	22
热板电功率 Heating Plate Heating Power	kW	14	16	18	20
总装机功率 Total Power	kW	29	35	44	46

本公司保留修改技术参数的权力, 恕不另行通知。  
DEKUMA reserves the right to change design and/or specifications without prior notice.

## 特点/Characteristics

- 高精度, 高产出, 超长使用寿命  
High precision, high output, extended service life
- 精密的零件和高品质的配套元件, 保证了机器超长使用寿命  
Precise components and high quality supporting parts extending service life
- 闭环温度控制保证了均匀的硫化过程  
Close-loop temperature control ensuring uniform vulcanizing process
- 注射, 塑化系统采用特殊结构设计, 确保注射量精确控制  
Specialized design of the injection and plasticizing unit ensuring precise control of injection volume
- 模块化设计可适应不同制品, 不同工艺及自动化要求  
Modular design can be configured for different articles, process requirement and automation
- 适合各种弹性体, 如天然胶, 三元乙丙胶, 高温硅橡胶, 氯丁胶等  
Suitable for all kind of elastomers like NR, EPDM, HTV, CR...

**德科橡塑科技(东莞)有限公司**  
DEKUMA RUBBER AND PLASTIC TECHNOLOGY (DONGGUAN) LTD.  
(大同机械有限公司成员 Member of Cosmos Machinery Ltd.)

地址: 广东省东莞市东城区周屋工业区银珠路 PC:523118  
Yinzhu Rd, Zhouwu Industrial Park, Dongcheng District,  
Dongguan, Guangdong, China

Tel: +86-769-2266 7222 / 7182 / 7208  
Website: www.dekuma.com

Fax: +86-769-2266 7227  
Email: info\_dkm@cml.com.cn